

Model Features	SMB Basic	SMB FXS/FXO	SMB E1	IP PBX 2010	Enterprise
FXO/FXS Ports	1 FXO	4 (up to 16)	-	Up to 500 Ports	Up to 4000 Ports
PRI	-	-	1	Up to 4	Up to 4
SIP Channels (Voipli lines)	15/30	15/30	30	90	120
Extensions. (remote and local)	50	50	50	500	5000
Full Interconnection With Coral/Panasonic	-	-	Digital	Digital	Digital
Intercom/ door open service	Yes		YES		YES
SIP Interconnectivity between IPPBX. Allows free calls within network.	Yes		Yes		Yes
Sip Trunk Capacity (Simultaneous outgoing Calls/bandwidth)	30/1Mb/sec		30/1Mb/sec		120/2Mb/sec
Conference Rooms/Participants	1 room/ 10 participants		5/30		unlimited
Codecs	G729/G711/GSM		G729/G711/GSM		G729/G711/GSM
Hard Disk (SATA)	SSD 16/32 GB		320 GB X 2		500 GB X 2
Redundancy/ RAID	SSD		Yes		Yes
CPU	Intel ATOM N270 1.7 GHz		Pentium Dual Core 2.8 GHz		Xeon Dual/ Quad Core 3+ GHz
RAM Existing/Expandable	1Gb/ DDR800		2Gb/ DDR800		4Gb/ DDR800
Power Supply/redundancy UPS	12 VDC, 1.5A, UPS Embedded (optional),		100-230 VAC 350W		2 X500W/yes
Operation System	Voipli 1.65 Linux based		Voipli 1.65 Linux based		Voipli 1.65 Linux Based
User Friendly Interface	Voipli Operation Panel (VOP)		VOP		VOP
Position	Horizontal/ Vertical (wall mounted)		Rack Mount. 1 U		Rack Mount. 2 U
Weight	1.500 Kg		3.5 Kg		18 Kg.